



SEVOLT HYDRO LUBE AW 32, 46, 68, 100, 150, 220, 320 & 460 (Hydraulic Oil)

SEVOLT DELTA HYDRO GM series oils are formulated with high quality lubricating oils. It is requirements of normal machinery and circulating systems for lubricating purpose.

	Test Properties	Test Method	SEVOLT DELTA HYDRO GM							
			ISO VG 32	ISO VG 46	ISO VG 68	ISO VG 100	ISO VG 150	ISO VG 220	ISO VG 320	ISO VG 460
Typical Properties & Characteristics	Appearance	Visual	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	28 - 32	44 - 49	66 - 70	95 - 105	145- 155	215- 225	310- 330	440- 480
	Viscosity Index	ASTM D 2270	90 Min	90 Min	90 Min	85 Min	85 Min	85 Min	85 Min	85 Min
	Flash Point, COC, °C	ASTM D 92	180 Min	180 Min	190 Min	200 Min	240 Min	240 Min	250 Min	250 Min

Packaging Options: SEVOLT DELTA HYDRO GM series is offered in 26, 50 & 210 Liter.

Properties:-

- Good oxidation stability and ageing resistance
- Rapid air release and low foaming
- Excellent corrosion protection for steel and non ferrous metals
- Good compatibility with sealing materials

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

