



SEVOLT ALFA TURBO 15W 40 API CI-4 PLUS

(Turbo Diesel Engine Oil)

SEVOLT ALFA TURBO 15W 40 CI-4 PLUS is formulated by highly saturated base oil & special type additives. It is extra high performance engine oil specially developed for enhanced wear protection, best corrosion protection; low emission trucks and busses application such as those used construction, agriculture and commercial services. Viscosity grade is high quality engine oil for use in high output, turbocharged diesel engines.

SEVOLT ALFA TURBO 15W40 is formulated to exceed API's latest specifications: Diesel engine oil specifications: CI-4 Plus.

SEVOLT ALFA TURBO 15W 40			
Test Properties		Test Method	SPECIFICATION
API SERVICE CATEGORY			CI-4 PLUS
SAE GRADE			15W-40
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.850 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	14 - 15
	Viscosity Index	ASTM D 2270	110 Min
	Pour Point, °C	ASTM D 97	-12 Max
	Flash Point, COC, °C	ASTM D 92	220 Min
	TBN, mg KOH/g	ASTM D 2896	10.0 Min

Packaging Options: SEVOLT ALFA TURBO 15W 40 is offered in 1, 5, 7.5, 10, 15, 20, 26, 50 & 210 Liters.

Properties:-

- CI-4 Plus is specifically formulated with higher technology which provides superior protection under savior condition.
- CI-4 Plus is specifically designed to give superior performance & protection even under extreme condition.
- Prolong engine life
- Superior soot control and acid neutralization.
- Protects against wear and corrosion
- Superior thermal and oxidation stability
- Reduce friction, sludge and varnish

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

The observance of all legal regulations and patents is the responsibility of the user.

