



SEVOLT GENERAL PURPOSE MACHINE OIL

Product	Kin. Viscosity cSt at 40 °C	Pour Point °C, Max.	Flash Point COC, °C Min.	Description / Application
Sevolt 22	20 – 24	-	150	<p>Sevolt oils are normally recommended for non-critical all loss lubrication systems and hand oiling applications involving lubrication of bearings, open gears, lightly loaded slides and guide ways of machine tools. Sevolt oils of appropriate viscosity are widely used in textile mills for lubrication of looms and other equipments, which do not require additive treated oils. These oils can also be used as fluid sealing medium for gas holder where the gases do not react with mineral oils and as filter media in oil-bath type air cleaners. Sevolt 22 is recommended for flushing of automotive and industrial equipments. The characteristics of Sevolt 22 make it possible to easily clean all inaccessible internal surfaces of various equipments.</p>
Sevolt 32	29 – 35	-	150	
Sevolt 46	42 – 50	-	160	
Sevolt 57	54 – 60	-	160	
Sevolt 68	62 – 74	-	160	
Sevolt 100	90 – 110	-	170	
Sevolt 150	135 – 165	-	204	
Sevolt 220	198 – 242	-	220	
Sevolt 320	288 – 352	-	220	
Sevolt 460	414 – 506	-	240	

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

The observance of all legal regulations and patents is the responsibility of the user.

