



SEVOLT ALL PURPOSE GREASE-2/3

SEVOLT ALL PURPOSE GREASE-2/3 are lithium soap multipurpose greases. Having high drop point, good thermal and structural stability. It has high degree of resistance to oxidation, rusting, corrosion and water washout. These greases are suitable for all automotive lubrication, universal joints & wheel bearings. These greases also find wide application in both antifriction and plain bearing of general machinery & farm equipment's.

| Properties | AP Grease - 2 | AP Grease - 3 |
|--|----------------|----------------|
| NLGI Grade | 2 | 3 |
| Appearance/Structure | Smooth & Tacky | Smooth & Tacky |
| Soap Type | Lithium | Lithium |
| Worked penetration @25 degree Celsius, after 60 strokes, 0.1 mm units, ASTM D217 | 270 | 235 |
| Drop Point, degree Celsius, ASTM D2265, Min. | 190 | 190 |
| Viscosity of Base Oil @40 degree Celsius, cSt, ASTM D445, Min. | 105 | 105 |
| Copper Strip Corrosion, ASTM D4048 | Negative | Negative |

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

