



SEVOLT CNG 20W-50

SEVOLT CNG 20W-50 is formulated with high quality paraffinic base stocks, detergents, dispersants, oxidation and corrosion inhibitors, antiwear and antifoam additive. Gold CNG 20W50 is high performance gas engine oil specially developed for vehicles running on environment friendly CNG & LPG fuels. The resulting oils meet or exceed the requirements of API Service Classification SE/ CC.

SEVOLT CNG 20W-50			
	Test Properties	Test Method	Specification
	API Grade		SE/CC
	SAE Grade		20W-50
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	3.0 Max
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.850 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	16.0 – 18.0
	Viscosity Index	ASTM D 2270	95 Min
	Pour Point, °C	ASTM D 97	-6 Max
	Flash Point, COC, °C	ASTM D 92	220 Min

Packaging Options: SEVOLT CNG 20W-50 series is offered in 0.5, 1, 26, 50 & 210 Liters.

Properties:-

- Excellent low as well as high temperature performance year round all weather.
- Excellent anti-corrosion and anti-wear properties
- High thermal and oxidation stability
- Highest wear protection
- Low oil consumption
- Increase engine life & reduce maintenance cost by performance additive used that reduces engine deposit.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

