



## SEVOLT GEAR SYN FLUID 80W-140

**SEVOLT GEAR SYN FLUID 80W-140** oil is fully synthetic, heavy duty, automotive gear oil and transmission oil suitable for use in cars, trucks, buses, construction plant and industrial applications. Available in SAE 80W-140 multi Viscosity grades, it meets the requirements of API gear oil classification GL -5 and specified for SAE J2360 (Formerly MIL-PRF-2105E) requirements. They are formulated from the highest quality polyolefin base oils and specified Additives.

SEVOLT GEAR SYN FLUID			
	<i>Test Properties</i>	<i>Test Method</i>	<i>80W-140</i>
<b>Typical Properties &amp; Characteristics</b>	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	1.0 Max
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.830 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	190 – 210
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	24 - 26
	Viscosity Index	ASTM D 2270	150 Min
	Pour Point, °C	ASTM D 97	-36 Max
	Flash Point, COC, °C	ASTM D 92	240 Min
	TAN, mg KOH/g	ASTM D 664	0.7 Min

**Packaging Options:** SEVOLT GEAR SYN FLUID 80W-140 is offered in 26, 50 & 210 Liter.

### Properties:-

- Good oxidation stability and ageing resistance
- Anti-rust and anti-corrosion qualities and anti-foam protection
- Superior load carrying and friction reducing properties
- Extended drain capability
- Exultant wear protection
- Good compatibility with sealing materials

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

The observance of all legal regulations and patents is the responsibility of the user.

