



SEVOLT GEC PLUS 20W50

SEVOLT GEC 20W50 is formulated with high quality paraffinic base stocks, detergents, dispersants, oxidation and corrosion inhibitors, antiwear and antifoam additive. The resulting oils meet or exceed the requirements of API Service Classification CF4. It is better performance provide compare then lower grade CF.

SEVOLT GEC. PLUS 20W50			
	Test Properties	Test Method	Specification
	API Grade		CF4
	SAE Grade		20W50
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.86 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	17 - 19
	Viscosity Index	ASTM D 2270	100 Min
	Pour Point, °C	ASTM D 97	-9 Max
	Flash Point, COC, °C	ASTM D 92	220 Min
	TBN, mg KOH/g	ASTM D 2896	5.0 Min

Packaging Options: SEVOLT GEC PLUS 20W50 is offered in 0.5, 01, 5, 26, 50 & 210 Liters

Properties:-

- Increased detergency in order to limit deposit formation on hot engine parts
- Strong dispersancy to avoid coalescence of combustion products
- High Total Base Number, giving full engine protection during the whole service period.
- Excellent anti-corrosion and anti-wear properties
- High thermal and oxidation stability
- Protection against bore polishing
- Low temperature fluidity which ensures easy starting and pumpability in winter

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

The observance of all legal regulations and patents is the responsibility of the user.

