



SEVOLT GEL CHASSIS GREASE-1/2/3

SEVOLT GEL CHASSIS GREASE-1/2/3 are lime based multipurpose grease. Gel Grease possesses excellent water resistant, anti rust & anti corrosive properties. They are recommended for general application & plain & anti friction bearing where temperatures are moderate. (Below 70 °C). This grease acts as protective layer on exposed parts. This grease is recommended for general chassis lubrication including suspension & steering system. It is also suitable for certain open & semi enclosed gears as well as chain drives of farm equipment's

Properties	Gel Chassis-1	Gel Chassis-2	Gel Chassis-3
NLGI Grade	1	2	3
Appearance/Structure	Shiny, Buttery Texture & Tacky	Shiny, Buttery Texture & Tacky	Shiny, Buttery Texture & Tacky
Soap Type	Calcium	Calcium	Calcium
Worked Penetration @25 Degree Celsius , after 60 strokes, 0.1 mm units, ASTM D217	320	272	235
Drop Point, Degree Celsius, ASTM D2265, Min.	100	105	105

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

