



## SEVOLT MOLY GREASE

**SEVOLT MOLY GREASE** are lime based multipurpose grease. Gel Grease possesses excellent water resistant, anti rust & anti corrosive properties. They are recommended for general application & plain & anti friction bearing where temperatures are moderate. (Below 70 Degree Celsius). This grease acts as protective layer on exposed parts. This grease is recommended for general chassis lubrication including suspension & steering system. It is also suitable for certain open & semi enclosed gears as well as chain drives of farm equipment's

Properties	Moly Grease
NLGI Grade	2
Appearance/Structure	Homogeneous, Smooth & Greyish Black
Soap Type	Lithium
Worked Penetration @25 Degree Celsius, after 60 strokes, 0.1mm units, ASTM D217	270
Drop Point, Degree Celsius, ASTM D2265, Min.	195
Viscosity of Base Oil @40 Degree Celsius, cSt, ASTM D445, Min.	150
Copper Strip Corrosion, ASTM D4048	Passes
Water Washout @79 Degree Celsius, ASTM D1264, % wt.	< 5
Four-Ball Weld Load, ASTM D2596, kg	315
MoS2 / Solid Content, % wt., ASTM D128, Min.	3

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

The observance of all legal regulations and patents is the responsibility of the user.

