



## SEVOLT PSO (Diesel Engine Oil)

**SEVOLT PSO** is blended from highly refined base stocks and a combination of anti-oxidant, anti-wear and anti-foam additives to meet the lubrication requirement of agriculture pump sets. This oil is recommended for agricultural pump sets, threshers, sugarcane harvesters / crushers etc. The resulting oils meet or exceed the requirements of API Service Classification CC and SE and U.S. Military specification MIL-L-2104B. It also meets the B.I.S specification, IS 13656, EDL-1.

<b>SEVOLT PSO</b>			
	<b>Test Properties</b>	<b>Test Method</b>	<b>Specification</b>
	<b>API Grade</b>		<b>CC/SE</b>
	<b>SAE Grade</b>		<b>20W-40</b>
<b>Specification &amp; Characteristics</b>	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Std. Red
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.870 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	13 – 15
	Viscosity Index	ASTM D 2270	90 Min
	Pour Point, °C	ASTM D 97	-6 Max
	Flash Point, COC, °C	ASTM D 92	220 Min
	TBN, mg KOH/g	ASTM D 2896	3.0 Min

**Packaging Options:** SEVOLT PSO is offered in 3.5, 26, 50 & 210 Liters.

**Properties:-**

- Good thermo-oxidative stability
- High detergency, anti-wear and anticorrosive properties
- Low maintenance cost
- Enhanced engine life

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

