



## SEVOLT ROTO SPIN 2, 5, 10, 12, 15 & 22

**SEVOLT ROTO SPIN** series oils are range of high quality spindle lubricants for use on modern textile machines. Manufactured from the highest quality base stocks and ashless additives, it reduces spindle wear, protects against rust and may be easily removed by washing textile contamination occurs.

		SEVOLT ROTO SPIN series						
<i>Test Properties</i>		<i>Test Method</i>	<i>ISO VG 2</i>	<i>ISO VG 5</i>	<i>ISO VG 10</i>	<i>ISO VG 12</i>	<i>ISO VG 15</i>	<i>ISO VG 22</i>
<b>Typical Properties &amp; Characteristics</b>	Appearance	Visual	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear
	Colour	ASTM D 1500	1.0 Max	1.0 Max	1.0 Max	1.0 Max	1.0 Max	1.0 Max
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.75 Min	0.80 Min	0.81 Min	0.82 Min	0.82 Min	0.82 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	2 Typ.	4 - 6	8 - 12	10 - 14	14 - 16	20 - 24
	Pour Point, °C	ASTM D 97	-21 Max	-21 Max	-21 Max	-21 Max	-15 Max	-15 Max
	Flash Point, COC, °C	ASTM D 92	100 Min	120 Min	170 Min	170 Min	180 Min	180 Min

**Packaging Options:** SEVOLT ROTO SPIN SERIES is offered in 26, 50 & 210 Liter.

### Properties:-

- Good oxidation stability and ageing resistance
- Rapid air release and low foaming
- Excellent corrosion protection for steel and non ferrous metals
- Easy removal of textile contamination by washing
- Easy start-up and minimum power loss.
- Low viscosity R & O type lubricants are specified

**Health & Safety:** Material Safety Data Sheet can be provided on request

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

The observance of all legal regulations and patents is the responsibility of the user.

