



## SEVOLT SUPER 4T PLUS 20W-40

**SEVOLT SUPER 4T PLUS**, SAE 20W-40 is a superior quality motor cycle oil engineered to enhance the power and performance of all the new age two-wheelers; meeting API SM, JASO T 903 MA-2 requirements. It provides longer engine life, smooth clutch operation and maximum gear & wears protection.

SEVOLT SUPER 4T PLUS			
Test Properties		Test Method	Specification
API Grade			SM
SAE Grade			20W-40
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Red
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.85 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	14 - 16
	Viscosity Index	ASTM D 2270	120 Min
	Pour Point, °C	ASTM D 97	-12 Max
	Flash Point, COC, °C	ASTM D 92	210 Min
	TBN, mg KOH/g	ASTM D 2896	5.0 Min

**Packaging Options:** SEVOLT SUPER 4T PLUS 20W-40 is offered in 0.9, 1, 20, 26, 50 & 210 Liters.

### Properties:-

- Possess special frictional properties required for smooth operation of wet clutches used in 4 stroke 2 wheelers
- Provide outstanding oxidation stability there by ensuring cleaner engine and extended oil life
- Good wear protection
- Minimize engine deposits due to excellent sludge and varnish control

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

