



SEVOLT SUPER KINTTING OIL 22 & 32 (N.W.)

SEVOLT SUPER KINTTING OIL 22 & 32 (N.W.) is formulated from paraffinic mineral oils and contains additives such as rust and oxidation inhibitors. These oils are developed to meet the critical requirements of modern sewing and industrial knitting machines. Textile applications including shearing, spindle, roving, knitting, Weaving, finishing and other related manufacturing.

SEVOLT SUPER KINTTING OIL				
	<i>Test Properties</i>	<i>Test Method</i>	<i>22</i>	<i>32</i>
Specification Properties & Characteristics	Appearance	Visual	Bright & Clear	Bright & Clear
	Colour	ASTM D 1500	0.5 Max	0.5 Max
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.820 Min	0.825 Min
	Viscosity, Kinematic at 40°C, cSt	ASTM D 445	20 - 24	27 - 33
	Viscosity, Kinematic at 100°C, cSt	ASTM D 445	3 – 4	5 – 6
	Viscosity Index	ASTM D 2270	100 min.	100 min.
	Pour Point, °C	ASTM D 97	-15 Max	-15 Max
	Flash Point, COC, °C	ASTM D 92	160 min.	180 min.
	Copper Corrosion @100°C	ASTM D 130	1a	1a

Packaging Options: SEVOLT SUPER KINTTING OIL 22 & 32 is offered in 50 & 210 Liter & Bulk supply.

Properties:-

- Very light in color & Non- washable.
- Excellent anti-rust capabilities.
- All machine speeds and needle type.
- Low co-efficient of friction
- Good lubrication characteristics

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

