



SEVOLT SYN FLUID 0W-20

SEVOLT SYN FLUID 0W-20 is a very high performance, synthetic diesel engine oil that provides excellent lubrication including long drain capability, helping towards long engine life for diesel engines operating in severe applications. The advanced technology behind this product delivers exceptional performance in turbo-charged as well as older naturally aspirated engines. The 0W-20 viscosity grade is one of the most recommended viscosity grades for new cars.

SEVOLT SYN FLUID 0W-20			
	Test Properties	Test Method	SPECIFICATION
	API SERVICE CATEGORY		SN/CI4-Plus
	SAE GRADE		0W-20
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Density @ 15, °C, g/ml	ASTM D 1298	0.815 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	7 - 9
	Viscosity Index	ASTM D 2270	150 Min
	Pour Point, °C	ASTM D 97	-51 Max
	Flash Point, COC, °C	ASTM D 92	220 Min
	TBN, mg KOH/g	ASTM D 2896	10.0 Min

Packaging Options: SEVOLT SYN FLUID 0W-20 is offered in 26, 50 & 210 Liters.

Properties:-

- Excellent wear protection in all driving condition
- Prolong engine life
- Fast lubrication at extremely low temperatures making start up easy
- Superior Active Cleansing Agents help remove built-up dirt and deposits
- Superior thermal and oxidation stability
- Reduce friction, sludge and varnish

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

