



## SEVOLT SYN FLUID 5W-50

**SEVOLT SYN FLUID 5W-50** is a fully synthetic motor oil ( not for 2 cycle ) using raw materials and advanced technology which guarantee complete reliability and high performance under all working conditions , including high speed highway or stop and go city driving.

SEVOLT SYN FLUID 5W-50			
	Test Properties	Test Method	SPECIFICATION
	<b>API SERVICE CATEGORY</b>		<b>SN/CI4</b>
	<b>SAE GRADE</b>		<b>5W-50</b>
<b>Specification &amp; Characteristics</b>	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.82 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	140 Max
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	17 - 18
	Viscosity Index	ASTM D 2270	140 Min
	Pour Point, °C	ASTM D 97	-30 Max
	Flash Point, COC, °C	ASTM D 92	220 Min
	TBN, mg KOH/g	ASTM D 2896	8.0 Min

**Packaging Options:** SEVOLT SYN FLUID 5W-50 is offered in 26, 50 & 210 Liters.

**Properties:-**

- Excellent wear protection in all driving condition
- Prolong engine life
- Fast lubrication at extremely low temperatures making start up easy
- Superior Active Cleansing Agents help remove built-up dirt and deposits
- Superior thermal and oxidation stability
- Reduce friction, sludge and varnish

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

