



SEVOLT SILICON GREASE-100

SEVOLT SILICON GREASE-100 is non-melting heavy consistency grease. This grease excellent thermal stability, Water repellency, Dielectric application chemical inertness and maintains its consistency over a wide temperature range. It has exceptional sealing ability which makes this grease ideal for vacuum & pressure system handling equipment's. In addition this grease is useful as lubricants for plastic, Rubber to Plastic & Rubber to Metal assemblies. Also it is used as releasing agent in epoxy, Polyester, PVC & Polystyrene moldings.

Properties	Silicon Grease-100
Appearance/Structure	Translucent White
Worked Penetration @25 Degree Celsius, after 60 Strokes, 0.1mm units, ASTM D217	220
Drop Point, Degree Celsius, ASTM D2265	Does not drop
Bleed, % 24 hrs. @200 Degree Celsius, Max	0.5
Evaporation, % loss 24 hrs. @200 Degree Celsius, ASTM D972, Max.	2
Operating Temperature Range, Degree Celsius.	-40/250 Degree Celsius

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

