



## SEVOLT ULTRA SUPER QUIENCHING OIL

**SEVOLT ULTRA SUPER QUIENCHING OIL** is general purpose straight mineral Quenching Oils manufactured from selected crudes of paraffin type. These grade are refined by an exclusive finishing process –an advance hydrogen refining process which enhances the higher resistance to oxidation, long service life and low carbon residue of these quenching oil Meets the requirement of IS 2664 -1980, Straight mineral Oils. These series are given below:-

**SEVOLT ULTRA SUPER QUIENCHING OIL** - It is use for fast quenching.

	<i>Test Properties</i>	<i>Test Method</i>	<b>Specification</b>
<b>Characteristics</b>	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	2.5 Max
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	16 - 20
	Flash Point, COC, °C, Min	ASTM D 92	150
	Fire Point, COC, °C, Min	ASTM D 92	156

**Packaging Options:** SEVOLT ULTRA SUPER QUIENCHING OIL is offered in 26, 50 & 210 Liter.

### Properties:-

- Good thermal properties
- Good chemical and oxidation stability
- High boiling points and low volatility
- High flash and fire points
- Good compatibility with sealing materials

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

The observance of all legal regulations and patents is the responsibility of the user.

