



SEVOLT UTTO

SEVOLT UTTO is Extra High Performance Diesel Engine oil specially developed for enhanced wear protection, superior corrosion protection and low emission for tractor. Gold UTTO is provides improved protection against wear and deposits and is suitable for use in wide range of on and offhighway applications where such type of lubricant is recommended.

SEVOLT UTTO			
	Test Properties	Test Method	SPECIFICATION
	API SERVICE CATEGORY		GL-4
	SAE GRADE		10W30
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.860 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	10 - 12
	Viscosity Index	ASTM D 2270	120 Min
	Pour Point, °C	ASTM D 97	-12 Max
	Flash Point, COC, °C	ASTM D 92	220 Min

Packaging Options: SEVOLT UTTO is offered in 1, 5, 7.5, 10, 15, 20, 26, 50 & 210 Liters.

Properties:-

- Better detergency reduces deposits and keep the engines cleaner
- Superior soot control and acid neutralization.
- Good corrosion inhibition properties provide Protection against wear and corrosion.
- Superior thermal and oxidation stability
- Reduce friction, sludge and varnish
- Prolong engine life

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

