



SEVOLT WHITE OIL INDUSTRIAL GRADES

SEVOLT WHITE OIL INDUSTRIAL GRADES are formulated from highly refined hydro treated base stocks. These are high purity hydrocarbons mixtures of alkanes in the C15 to C40 range and essentially of colorless, odourless. It is used only for industrial purposes not directly related to human being.

SEVOLT WHITE OIL					
	<i>Test Properties</i>	<i>Test Method</i>	12	32	100
Properties & Characteristics	Appearance	Visual	Bright & Clear	Bright & Clear	Bright & Clear
	Colour	ASTM D 1500	0 Max	0 Max	0 Max
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.810 Min	0.820 Min	0.840 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	11 - 14	28 - 32	85 - 100
	Viscosity Index	ASTM D 2270	100 Min	100 Min	100 Min
	Pour Point, °C	ASTM D 97	-15 Max	-15 Max	-12 Max
	Flash Point, COC, °C	ASTM D 92	160 Min	200 Min	240 Min

Packaging Options: SEVOLT WHITE OIL series is offered in 210 Liter & Bulk Supply

Properties:-

- Good oxidation stability and ageing resistance
- Rapid air release and low foaming
- Good compatibility with sealing materials

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

