



SEVOLT G.E.C. 20W-40 (Heavy Duty Engine Oil)

SEVOLT GEC 20W-40 is formulated with high quality paraffinic base stocks, detergents, dispersants, oxidation and corrosion inhibitors, antiwear and antifoam additive. The resulting oils meet or exceed the requirements of API Service Classification CF and SF and BIS specification, IS 13656-2002, EDL-2/EPL 2.

SEVOLT GEC 20W-40			
	TEST PROPERTIES	TEST METHOD	SPECIFICATION
	API GRADE		CF/SF
	SAE GRADE		20W-40
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Std. Red
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.85 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	14 - 15
	Viscosity Index	ASTM D 2270	100 Min
	Pour Point, °C	ASTM D 97	-6 Max
	Flash Point, COC, °C	ASTM D 92	210 Min
	TBN, mg KOH/g	ASTM D 2896	4.0 Min

Packaging Options: SEVOLT GEC 20W-40 series is offered in 7.5, 10, 15, 20, 26, 50 & 210 Liters.

Properties:-

- Effective antiwear characteristics protect engine components
- Good detergency characteristics ensure cleaner engine
- Better corrosion inhibition properties offer protection against rust and corrosion

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. The observance of all legal regulations and patents is the responsibility of the user.

